

Section 1: Identification

- (a) Glow Tint All Colors - #1, #2, #3, #4, #5, #6 (pints)
- (b) Accessory Embalming Chemical
- (c) For use by professional licensed embalmers only
- (d) Manufacturer: TNPC, LLC – Dallas, TX 75236
- (e) Privately labeled for & distributed by: Pierce Companies – 4722 Bronze Way – Dallas, TX 75236 – 214.333.4230
- (f) Emergency Phone Number: CHEMTREC - 800.424.9300

Section 2: Hazard Identification

- (a) **OSHA/HCS status:** This material is considered hazardous by the OSHA Hazard Communication Standard (29 CFR 1910.1200).
- (b) **DANGER!** Flammable Liquid and Vapor; Pungent odor



Section 3: Composition/Information on Ingredients

CHEMICAL NAME	CAS NUMBER	%	Trade Secret Information: Exact % of concentration is withheld to protect Trade Secret Information. Ranges are given in accordance with CFR 29 1910.1200(i), Appendix E
Isopropyl Alcohol	67-63-0	65 - 90	

Section 4: First-Aid Measures

Inhalation: Move to fresh air. Treat symptomatically. Get medical attention if symptoms persist.

Eyes: Immediately flush with plenty of water for at least 15 minutes. If easy to do, remove contact lenses. Get medical attention. In case of irritation from airborne exposure, move to fresh air. Get medical attention if symptoms persist.

Skin: Wash with soap and water. Remove contaminated clothing and shoes. Get medical attention if symptoms occur. Wash contaminated clothing before reuse. Thoroughly clean shoes before reuse.

Ingestion: Seek medical advice.

Section 5: Fire-fighting Measures

NFPA: Health: 2 Flammability: 3 Chemical Reactivity: 0

Extinguishing Media: water spray, dry chemical, carbon dioxide, alcohol foam

Special Fire-Fighting Procedures: Wear self-contained breathing apparatus and protective clothing. Fight fire from a protected location. Water may be ineffective in fighting the fire. Use water spray to keep fire-exposed containers cool.

Hazardous Combustion Products: Carbon dioxide, carbon monoxide.

Unusual Fire and Explosion Hazards: Vapors may cause a flash fire or ignite explosively. Vapors may travel considerable distance to a source of ignition and flash back. Prevent buildup of vapors or gases to explosive concentrations. Forms explosive peroxides which may be shock sensitive.

Section 6: Accidental Release Measures

Use personal protective equipment. Eliminate all ignition sources. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste.

For large spills: Use water spray to disperse vapors and dilute spill to a nonflammable mixture. Prevent runoff from entering drains, sewers, or streams. Dike for later disposal.

Section 7: Handling and Storage

Personal Precautionary Measures: Avoid breathing high vapor concentrations. Avoid contact with eyes and prolonged or repeated contact with skin. Do not taste or swallow. Use only with adequate ventilation. Wash thoroughly after handling.

Prevention of Fire and Explosion: Keep away from heat, sparks, and flame. Keep from contact with oxidizing materials. Use only with adequate ventilation. Comply with all national, state, and local codes pertaining to the storage, handling, dispensing and disposal of flammable liquids. Do not expose to air. After opening, purge container with nitrogen before reclosing. Periodically test for peroxide formation on long-term storage. If peroxide formation is suspected, do not open or move container. Do not allow to evaporate to near dryness. Distill with caution. Addition of water or appropriate reducing materials will lessen peroxide formation.

Storage: Keep container tightly closed and in a well-ventilated place.

Additional Information: Store away from heat and light.

Section 8: Exposure Controls/Personal Protection

CHEMICAL NAME	CAS NUMBER	PEL OSHA	TLV-ACGIH
Isopropyl Alcohol	67-63-0	400 ppm, 980 mg/m ³	400 ppm, 980 mg/m ³ 500 ppm, 1225 mg/m ³

Country specific exposure limits have not been established or are not applicable unless listed below.

ISOPROPYL ALCOHOL

- US NIOSH: Pocket Guide to Chemical Hazards
Recommended exposure limit (REL): 400 ppm, 980 mg/m³
- US NIOSH: Pocket Guide to Chemical Hazards
Short Term Exposure Limit (STEL): 500 ppm; 1,225 mg/m³
- US OSHA Table Z-1 Limits for Air Contaminants (29 CFR 1910.1000)
PEL: 400 ppm, 980 mg/m³
- US ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values
Time Weighted Average (TWA): 200 ppm
- US ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values
Short Tem Exposure Limit (STEL): 400 ppm

ISOPROPANOL (ISOPROPYL ALCOHOL)

- US ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values
Time Weighted Average (TWA): 200 ppm
- US ACGIH Notice of Intended Changes (NIC) to Threshold Limit Values
Short Term Exposure Limit (STEL): 400 ppm

Safety Data Sheet: Glow Tint All Colors (Item #PW0447600-605)

PROPANOL

US ACGIH Threshold Limit Values

Time Weighted Average (TWA): 200 ppm

US ACGIH Threshold Limit Values

Short Term Exposure Limits (STEL): 400 ppm

Ventilation: Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to condition. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been establishing, maintain airborne levels to an acceptable level.

Respiratory Protection: If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. In the United States of America, if respirators are used, a program should be instituted to assure compliance with OSHA Standard 63 FR 1152, January 8, 1998. Respirator type: Air-purifying respirator with an appropriate, government approved (where applicable), air-purifying filter, cartridge, or canister. Contact health and safety professional or manufacturer for specific information.

Eye Protection: Wear safety glasses with side shields (or goggles). Wear a full-face respirator, if needed.

Skin Protection: For operations where prolonged or repeated skin contact may occur, chemical-resistant gloves should be worn. Contact health and safety professional or manufacturer for specific information.

Recommended Decontamination Facilities: Eye bath, washing facilities, safety shower.

Section 9: Physical and chemical properties

FLASH POINT: 55°F (ASTM D93)

BOILING POINT: 186°F

EVAPORATION RATE (BUTYL ACETATE=1): <1

MELTING POINT: No information

pH: 6.16

SOLUBILITY IN WATER: Soluble

FLAMMABLE LIMITS: LEL=2% UEL=12.7%

SPECIFIC GRAVITY (WATER=1): .839 g/ml @72°

VAPOR DENSITY (AIR=1): 2.10

VAPOR PRESSURE (mm HG): 97.10 mm Hg @ 72°F

% VOLATILE BY WEIGHT: 34.95%

APPEARANCE AND ODOR INFORMATION: Orange to reddish purple liquid

Section 10: Stability and Reactivity

UNSTABLE: NO **STABLE:** YES. Forms explosive peroxides on concentration.

INCOMPATIBILITY: Material reacts violently with strong oxidizing agents, Crotonaldehyde

HAZARDOUS POLYMERIZATION: Will not occur **CONDITIONS TO AVOID FOR POLYMERIZATION:** Not applicable.

Section 11: Toxicological Information

Skin: This material has a low potential to cause allergic skin reactions; however, cases of human skin sensitization have been reported. Acute toxicity data, if available, are listed below. Additional toxicity data may be available on request.

Oral LD-50: (rat)	5,800 mg/kg
Oral LD-50: (rabbit)	7,900 mg/kg
Oral LD-50: (dog)	6,200 mg/kg
Inhalation LC-50: (rat)	8 h: 12000 ppm
Skin Irritation (rabbit)	slight
Eye irritation (rabbit)	moderate

Section 12: Ecological Information

Acute toxicity data, if available, are listed below. Additional toxicity data may be available on request.

Oxygen Demand Data:

BOD-5: 1,190 – 1,720 mg/g

BOD-20: 1,680 m/g

COD (Chemical Oxygen Demand): 2,230 mg/g

ThBOD: 2,400 mg/g

Acute Aquatic Effects Data:

96 h LC-50 (fathead minnow): > 100 u1/L

48 h LC-50 (golden orfe): 8970 – 9280 mg/L

96 h LC-50 (daphnid): > 1000 u1/L


Section 13: Disposal Considerations

Discharge, treatment, or disposal may be subject to national, state, or local laws. Incinerate. Since emptied containers retain product residue, follow label warnings even after container is emptied. Residual vapors may explode on ignition; do not cut, drill, grind, or weld on or near this container.

Empty bottles: DO NOT RECYCLE!

Section 14: Transport Information

DOT/UN HAZARD CLASSIFICATION: N/A



Section 15: Regulatory Information

SARA 311-312 Hazard classification(s): immediate (acute) health hazard; fire hazard

SARA 313: none, unless listed below.

Carcinogenicity Classification (components present at 0.1% or more): none, unless listed below.

TSCA (US Toxic Substances Control Act): This product is listed on the TSCA inventory. Any impurities present in this product are exempt from listing.

DSL (Canadian Domestic Substances List) and CEPA (Canadian Environmental Protection Act): This product is listed on the DSL. Any impurities present in this product are exempt from listing.

Safety Data Sheet: Glow Tint All Colors (Item #PW0447600-605)

EINECS (European Inventory of Existing commercial Chemical Substances): This product is listed on EINECS or otherwise complies with EINECS requirements. EINECS Number: 200-661-7

AICS / NICNAS (Australian Inventory of Chemical Substances and National Industrial Chemicals Notification and Assessment Scheme): This product is listed on AICS or otherwise complies with NICNAS.

MITI (Japanese Handbook of Existing and New Chemical Substances): This product is listed in the Handbook or has been approved in Japan by new substance notification.

ECL (Korean Toxic Substances Control Act): This product is listed on the Korean Toxic Substances Control Act: This product is listed on the Korean inventory or otherwise complies with the Korean Toxic Substances Control Act.

Philippines Inventory (PICCS): This product is listed on the Philippine Inventory or otherwise complies with PICCS.

Inventory of Existing Chemical Substances in China: All components of this product are listed on the Inventory of Existing Chemical Substances in China (IECSC).

Section 16: Other Information

Hazardous Material Information System III (USA)

Health:	2
Flammability:	3
Chemical Reactivity:	1

National Fire Protection Association (USA)

Health:	2
Flammability:	3
Chemical Reactivity:	1

HMIS ratings are based on a 0-4 scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. Although HMIS ratings are not required on Safety Data Sheets under 29 CFT 1910.1200, the preparer may choose to provide them. HMIS ratings are to be used with a fully implemented HMIS program. HMIS is a registered mark of the National Paint & Coatings Association (NPCA).

Prepared by:	Pierce Companies Regulatory Department
Date of Preparation/Revision:	June 01, 2023
Supersedes:	October 19, 2017

Notice: The information provided herein was believed by Pierce Companies ("Pierce") to be accurate at the time of preparation or prepared from sources believed to be reliable, accurate to the best of our knowledge. We do not suggest or guarantee that any hazards listed herein are the only ones which exist. It is the responsibility of the user to investigate and understand other pertinent sources of information, to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. Pierce makes no warranty of any kind, express or implied, concerning the safe use of this material in your process or in combination with other substances. Effects can be aggravated by other materials and/or this material may aggravate or add to the effects of other materials. This material may be released from gas, liquid or solid materials made directly or indirectly from it. User has the sole responsibility to determine the suitability of the materials for any use and the manner of use contemplated. User must meet all applicable safety and health standards. All products supplied by Pierce are subject to Pierce's terms and conditions of sale. **PIERCE MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY PIERCE**, except that the product shall conform to Pierce's specifications. Nothing contained herein constitutes an offer for the sale of any product. Safety Data Sheets are provided on the Internet by Pierce as a service to its customers. Possession of a Safety Data Sheet does not indicate that the possessor of the Safety Data Sheet was a purchaser or user of the subject product.