



# SAFETY DATA SHEET

## Tissue Filler (Liquid Tissue)

Labeled for & Distributed by:  
Pierce  
4722 Bronze Way, Dallas, TX 75236  
214.333.4230

Packaged by



PTHPACKAGING

### 1. PRODUCT AND COMPANY IDENTIFICATION

<b>DATE ISSUED:</b>	6/9/2023
<b>SDS REF. No:</b>	2571-CL-116

**PRODUCT NAME:** Tissue Filler

**PRODUCT CODE:** 2571-CL-116

**SYNONYMS:**

**CAS NUMBER:**

**PRODUCT USE:** Thinner

**MANUFACTURER:**

CIC Coatings, LLC  
2935 Almeta Ln

McKinney, TX,  
877-258-8797

**24 HR. EMERGENCY TELEPHONE NUMBER**

**ChemTel :** (800)255-3924

### 2. HAZARDS IDENTIFICATION

#### GHS Classification:

Flammable liquid  
Specific Target Organ Toxicity (single exposure)  
Eye irritation

Category 2  
Category 3  
Category 2

#### Hazard Symbols:



**Single word:** Danger

#### Hazard statements:

Highly flammable liquid and vapor  
Harmful if inhaled  
Causes skin irritation  
Causes serious eye irritation



# SAFETY DATA SHEET

## Tissue Filler



May cause damage to organs through prolonged or repeated exposure.  
May cause long lasting harmful effects to aquatic life.  
May be fatal if swallowed and enters airways.

### Precautionary statements:

#### Prevention:

Use only in well ventilated area.  
Control of exposure by mechanical ventilation in an unventilated or confined space.  
Avoid breathing vapors and contact with skin and eyes.  
Wear breathing apparatus/protective gloves/face protection.  
Store in well-ventilated place.  
Disposal must be in accordance with applicable federal, state, or local regulations.

#### Response:

IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell. Rinse mouth.  
IF ON SKIN: Wash with plenty of soap and water. Call a POISON CENTER or doctor/ physician if you feel unwell.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
If skin irritation occurs: Get medical advice/ attention.  
If eye irritation persists: Get medical advice/ attention.  
Take off contaminated clothing and wash before reuse.  
In case of fire: Use dry sand, dry chemical or alcohol resistant foam to extinguish.

#### Storage:

Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.

#### Disposal:

Dispose of contents/ container to an approved waste disposal plant.

### Other hazards:

None Known.



# SAFETY DATA SHEET

## Tissue Filler



### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Concentration (% wt)
Methyl Alcohol	67-56-7	90-100%

There are no additional ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

### 4. FIRST AID MEASURES

#### Description of necessary first aid measures

Eye:

1. Flush immediately with warm water for at least 20 minutes.
2. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.
3. If pain persists or recurs seek medical attention.
4. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.

Skin:

1. Removing contaminated clothing, shoes, and leathery wearings, cleaning procedure is available before reused or waste treatment.
2. Washing affected area thoroughly with soap and water for at least 20 minutes.
3. Call a Physician if irritation develops or persists.

Ingestion:

1. If spontaneous vomiting appears imminent or occurs, hold patient's head down, lower than their hips to help avoid possible aspiration of vomits.
2. If victim is conscious and alert, give 24 cupfuls of milk/water to dilute the substance in stomach.
3. Never give anything by mouth to an unconscious person.
4. Don't induce vomiting unless directed to do so by medical person.
5. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration.
6. Then seek for medical attention.

Inhalation:

1. Remove from further exposure and flush thoroughly with air.
2. Lay patient down. Keep warm and rested.



# SAFETY DATA SHEET

## Tissue Filler



3. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures.
4. If respiratory irritation, seek immediate medical assistance and call a physician.

### **Most important symptoms/effects, acute and delayed:**

Headache, fatigue, drowsiness, insomnia, anorexia and pain in limbs, nervousness, impairment of memory.

### **Indication of immediate medical attention and special treatment needed, if necessary For acute or short term repeated exposures:**

Inhalation:

1. Inhalation overexposure can produce toxic effects. Monitor for respiratory distress.
2. If cough or difficulty in breathing develops, evaluate for upper respiratory tract inflammation, bronchitis, and pneumonitis. Administer supplemental oxygen with assisted ventilation, as required.
3. This material (or a component) sensitizes the heart to the effects of sympathomimetic amines. Epinephrine and other sympathomimetic drugs may initiate cardiac arrhythmias in individuals exposed to this material.
4. Administration of sympathomimetic drugs should be avoided.

Ingestion:

1. If ingested, this material presents a significant aspiration and chemical pneumonitis hazard.
2. Induction of emesis is not recommended.
3. Consider activated charcoal and/or gastric lavage.
4. If patient is obtunded, protect the airway by cuffed endotracheal intubation or by placement of the body in a Trendelenburg and left lateral decubitus position.

## **5. FIRE FIGHTING MEASURES**

**Flash Pt:** 54 F Method Used: TAG Closed Cup

**Explosive Limits:** LEL: 2.5 % at 77.0 F UEL: 13.0 % at 77.0 F

**Auto ignition Pt:** 869.00 F

**Extinguishing media:**

Foam, CO<sub>2</sub>, Dry chemical, Water fog.



# SAFETY DATA SHEET

## Tissue Filler



### Special protective equipment and precautions for fire-fighters:

1. Firefighters must use full bunker gear including NIOSH-approved positive pressure self-contained breathing apparatus to protect against potential hazardous combustion or decomposition products and oxygen deficiencies.
2. Evacuate area and fight the fire from a maximum distance or use unmanned hose holders or monitor nozzles.
3. Cover pooling liquid with foam.
4. Containers can build pressure if exposed to radiant heat; cool adjacent containers with flooding quantities of water until well after the fire is out.
5. Withdraw immediately from the area if there is a rising sound from a venting safety device or discoloration of vessels, tanks, or pipelines.
6. Be aware that burning liquid will float on water.
7. Notify appropriate authorities of potential fire and explosion hazard if liquid enter sewers or waterways

## 6. ACCIDENTAL RELEASE MEASURES

### Personal precautions, protective equipment and emergency procedure:

1. Personal protective equipment (specified in Section 8)

Eyes: Chemical safety goggles are recommended, and a face shield is added when needed.

Skin: Wear appropriate protective gloves to avoid skin contact.

Clothing: When direct contact is likely, use rubberized clothing, apron and boots.

Respiratory: When limits are exceeded, wear a respirator approved by NIOSH/MSHA for protection against organic dust, mists and vapors.

2. Remove all sources of ignition. No smoking, naked lights or ignition sources. Ventilate area of leak or spill.

3. Keep unnecessary and unprotected personnel from entering. Evacuate personnel from the danger area. Consult with an expert about the emergency procedures.

### Environmental precautions:

1. Prevent spillage from entering drains, surface, and groundwater.
2. Contain and recover liquid when possible. Use non-sparking tools and equipment.
3. Collect liquid in an appropriate container or absorb with an inert material (e.g. vermiculite, dry sand, earth), and place in a chemical waste container.
4. Report the accidental spill/release to Local/State government.



# SAFETY DATA SHEET

## Tissue Filler



### Methods and materials for containment and cleaning up

#### Minor spill:

1. Remove all ignition sources.
2. Clean up all spills immediately.
3. Avoid breathing vapors and contact with skin and eyes.
4. Control personal contact by using protective equipment.
5. Contain and absorb small quantities with vermiculite or other absorbent material.
6. Wipe up.
7. Collect residues in a flammable waste container.

#### Major spill:

1. Clear area of personnel and move upwind.
2. Alert emergency responders and tell them location and nature of hazard.
3. May be violently or explosively reactive.
4. Wear breathing apparatus plus protective gloves.
5. Prevent spillage from entering drains or water course.
6. No smoking, naked lights or ignition sources. Increase ventilation.
7. Stop leak if safe to do so.
8. Water spray or fog may be used to disperse/absorb vapor.
9. Contain spill with sand, earth or vermiculite.
10. Use only spark-free shovels and explosion proof equipment.
11. Collect recoverable product into labeled containers for recycling..
12. Absorb remaining product with sand, earth or vermiculite.
13. Collect solid residues and seal in labeled drums for disposal.
14. Wash area and prevent runoff into drains.
15. If contamination of drains or waterways occurs, advise emergency services.

## 7. HANDLING AND STORAGE

### Precautions for safe handling:

1. Wash thoroughly after handling.
2. Use only in well ventilated area.
3. Ground and bond containers when transferring.
4. Use spark-free tools and explosion proof equipment.
5. Empty containers retain product residue (liquid/vapor), and can be dangerous.
6. Do not pressurize, cut, weld, braze, solder, drill, or expose empty containers to heat, sparks or open flames.

### Conditions for safe storage, including any incompatibilities:

1. Store in original containers in approved flame-proof area.
2. No smoking, naked lights, heat or ignition sources.
3. DO NOT store in pits, depressions, basements or areas where vapors may be trapped.



# SAFETY DATA SHEET

## Tissue Filler



4. Keep containers securely sealed.
5. Store away from incompatible materials in a cool, dry well ventilated area.
6. Protect containers against physical damage and check regularly for leaks.
7. Keep containers tightly closed and store in a cool, dry, well-ventilated place, plainly labeled, and out of closed vehicles.
8. Ground all equipment containing this material.
9. Observe manufacturer's storing and handling recommendations.
10. Containers should be able to withstand pressures expected from warming and cooling in storage. This flammable liquid should be stored in a separate safety cabinet or room. A refrigerated room is preferable for materials with a flash point temperature lower than 70°F (21°C).

### 8. EXPOSURE CONTROLS\PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Methyl Alcohol	67-56-7	TWA	200 PPM	ACGIH TLV
		TWA	200 ppm 260 mg/m <sup>3</sup>	OSHA PEL
		TWA	200 PPM 260 mg/m	NIOSH IDLH

#### Engineering control:

1. Process should be located at least 17 meter (50 feet) away from open flames and all high temperature operations likely to cause ignition of the styrene monomer vapor.
2. In venting styrene monomer vapors, consideration should be given to possible halogenation of the vapors by low concentrations of free chlorine and bromine with the resultant formation of lacrimations.
3. Process should be designed so that the operator is not exposed to direct contact with Toluene or the vapor. The technical problems of designing equipment, providing adequate ventilation and operating procedures which promise maximum security and economy, can best be handled by competent engineers.
4. It is essential for safety that equipment be used and maintained as recommended by the manufacturer.
5. Tanks used to store or process Toluene should be closed vessels vented to a safe point of discharge in the outside atmosphere away from operating stations, roadways, and at least 17



# SAFETY DATA SHEET

## Tissue Filler



meter (50 feet) from possible sources of ignitions. All sparks, flames, heated surface, or other sources of ignition should be kept away from all vents. It is advisable, to provide suction on vessels when inspection or observation openings are made, to minimize or eliminate escape of vapors.

### Personal protective equipment:

#### Eye Protection:

Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. Chemical goggles should be worn during transfer operations or when there is a likelihood of misting, splashing, or spraying of this material. A suitable emergency eye wash water and safety shower should be located near the work station.

#### Skin protection:

Wear impervious protective clothing, including boots, gloves, lab coat, apron or coveralls, as appropriate, to prevent skin contact.

#### Clothing:

Avoid skin contact. Wear long-sleeved fire-retardant garments (e.g., Nomex®) while working with flammable and combustible liquids. Additional chemical-resistant protective gear may be required if splashing or spraying conditions exist. This may include an apron, boots and additional facial protection. If product comes in contact with clothing, immediately remove soaked clothing and shower. Promptly remove and discard contaminated leather goods.

#### Respirators:

For known vapor concentrations above the occupational exposure guidelines (see below), use a NIOSH-approved organic vapor respirator if adequate protection is provided. Protection factors vary depending upon the type of respirator used. Respirators should be used in accordance with OSHA requirements (29 CFR 1910.134). For airborne vapor concentrations that exceed the recommended protection factors for organic vapor respirators, use a full-face, positive-pressure, supplied air respirator. Due to fire and explosion hazards, do not enter atmospheres containing concentrations greater than 10% of the lower flammable limit of this product.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

**PHYSICAL STATE:** Liquid

**COLOR:** Pigmented

**ODOR:** Ketone odor, sweet pungent odor.

**pH:** n/a





# SAFETY DATA SHEET

## Tissue Filler



**BOILING POINT:** >155 F

**FREEZING POINT:** -95 C

**FLASH POINT:** 54 F (closed cup)

**VOLATILE ORGANIC COMPOUNDS:** 773 lbs/gal

(VOC Theoretical – As Packaged)

**SOLUBILITY IN WATER:** Readily

**DENSITY (Lb/Gal):** 6.83

**EVAPORATION RATE:** No further relevant information available

**SPECIFIC GRAVITY:** .82

### 10. STABILITY AND REACTIVITY

**Reactivity:**

Vapor is explosive when exposed to heat or flame

**Chemical stability:**

Stable at room temperature in closed containers under normal storage and handling conditions.

Possibility of hazardous reaction

Has not been reported.

**Condition to avoid:**

Product is highly flammable – Keep away from sources of ignition. Avoid the higher temperatures. Keep away from open fire, heating elements and heat radiating surface and prevent from forming of the vapours mixtures with air in explosion limits.

**Incompatible materials:**

Heat, flame, strong oxidizers, nitric and sulfuric acids, chlorine, nitrogen tetroxide; will attack some forms of plastics, rubber, coatings.

**Hazardous decomposition products:**

Carbon monoxide, carbon dioxide, hydrocarbons.

### 11. TOXICOLOGICAL INFORMATION

**ACUTE TOXICITY:**



# SAFETY DATA SHEET

## Tissue Filler



**Chemical Name**

**WT %**

**Methyl Alcohol**  
(67-56-1)

90-100%

Acute Oral Toxicity	100.1 mg/kg ( Mouse )
Acute Inhalation Toxicity	20000 ppm/10H ( Rat)
Acute dermal Toxicity	Not Listed

**Acute effects:**

EYE: Causes Serious Eye Irritation

SKIN: Causes skin irritation. Allergic reactions are possible.

INHALATION: Harmful if inhaled. High gas, vapor, mist or dust concentrations may be harmful if inhaled. Avoid breathing fumes, spray, vapors, or mist. High vapor concentrations are irritating to the eyes, nose, throat and lungs.

INGESTION: Harmful if swallowed.

**Chronic effect:**

Carcinogenicity:  
ACGIH :  
OSHA : Not listed  
IARC :

Reproductive Effects: Not available.

Neurotoxicity: Not available.  
Mutagenicity: Not available.

## 12. ECOLOGICAL INFORMATION



# SAFETY DATA SHEET

## Tissue Filler



### Ecotoxicity:

Fish:

Oncorhynchus mykiss: LC50= 5540 mg/l 96h

Alburnus alburnus: LC50 =11000 mg/l 96h

Leuciscus idus: LC50 =11300 mg/L/48h

Salmo gairdneri: LC50 =6100 mg/L/24h

Water flea:

EC50 = 8800 mg/L/48h

EC50 = 12700 mg/L/48h

EC50 = 12600 mg/L/48h

Freshwater Algae: NOEC = 430 mg/l (algae; 96h)

**Persistence and Degradability:** Persistence is unlikely based on information available.

**Bioaccumulation/ Accumulation:** No information available.

**Mobility:** Will likely be mobile in the environment due to its volatility.

### 13. DISPOSAL CONSIDERATIONS

**RECOMMENDATIONS:** The generation of waste should be avoided or minimized wherever possible. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional

**SAFE HANDLING:** Dispose of in accordance with federal, state, provincial, and local regulations. Local requirements may vary, consult your sanitation department or state-designated environmental protection agency for more disposal options.

### 14. TRANSPORT INFORMATION

DOT

IMDG

IATA



# SAFETY DATA SHEET

## Tissue Filler



<b>UN Number</b>	1263	1263	1263
<b>Proper shipping Name</b>	Paint, Flammable Liquid	Paint, Flammable Liquid	Paint, Flammable Liquid
<b>Hazard Class</b>	3	3.2	3.2
<b>Packing Group</b>	II	II	II
<b>Marine Pollutant</b>	NO	NO	NO

**\*\*\* CIC Coatings, LLC verifies that the material was supplied and shipped in the proper packages in accordance with DOT and federal regulations that are applicable to the mode of transportation selected. The shipper must verify that the packaging supplied is acceptable to be re-shipped in per the federal regulations applicable to the mode of transportation for reshipment. Regulations may change depending on mode of transportation selected.\*\*\***

### 15. REGULATORY INFORMATION

#### U.S. Federal Regulations

**TSCA 12(b):** Not applicable

**SARA 313:** This product contains the following chemicals subject to the reporting requirements of SARA Title III, Section 313 and 40 CFR 372:

<u>Component Reporting</u>	<u>Threshold</u>
Methyl Alcohol 90-100%	

#### **SARA 311/312 Hazardous Categorization**

**Acute Health Hazard:** Yes

**Chronic Health Hazard:** Yes

**Fire Hazard:** Yes

**Sudden Release of Pressure Hazard:** No

**Reactive Hazard:** No

**Clean Water Act:** Not applicable

**Clean Air Act:** Not applicable

**OSHA:** Not applicable

**CERCLA:** This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

**Component Hazardous Substances:** Acetone 5000 lb

**California Proposition 65:** Methyl Alcohol which is/are known to the State of California to cause birth defects or other reproductive harm

#### **State Right-to-Know:**

Massachusetts, New Jersey, Pennsylvania, Illinois, Rhode Island

#### U.S. Department of Transportation

**Reportable Quantity (RQ):** Y  
**DOT Marine Pollutant:** N  
**DOT Severe Marine Pollutant:** N

**U.S. Department of Homeland Security, this product contains the following DHS chemicals:**

**Other International Regulations**

**Mexico - Grade** Serious risk, Grade 3


**Canada:** This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

**WHMIS Hazard Class** B2 Flammable liquid, D2B Toxic materials

**16. OTHER INFORMATION**

HMIS RATING	
Health :	2
Flammability :	3
Reactivity :	0
Personal Protection :	I

**NFPA CODES**



**REVISION INDICATOR :** No Data Available

**MANUFACTURER DISCLAIMER:** To the best of CIC Coatings, LLC knowledge, all information, recommendations, and suggestions appearing herein concerning this product are taken from raw material sources or based upon data believed to be reliable.

**Legend**

- ACGIH: American Conference of Governmental Industrial Hygienists
- CAS No.: Chemical Abstract Service Registry Number
- CERCLA: Comprehensive Environmental Response, Compensation and Liability Act (U.S. EPA)
- CPR: Controlled Product Regulations (Canada)
- DOT: Department of Transportation (U.S.)
- EPA: Environmental Protection Agency (U.S.)
- GHS: Globally Harmonized System of Classification and Labeling of Chemicals
- HEPA: High-Efficiency Particulate Air
- HMIS: Hazardous Materials Identification System
- IARC: International Agency for Research on Cancer
- IATA: International Air Transport Association
- IMDG: International Maritime Dangerous Goods code
- LPP: Limité Permissible Ponderado (Chile)
- NIOSH: National Institute of Occupational Safety and Health (U.S.)
- NFPA: National Fire Protection Association (US)
- NTP: National Toxicology Program (US)
- OSHA: Occupational Safety and Health Administration (U.S.)
- PEL: Permissible Exposure Limit
- SARA: Superfund Amendments and Reauthorization Act (U.S. EPA)
- SDS: Safety Data Sheet
- STEL: Short Term Exposure Limit (15 minute Time Weighted Average)
- STOT: Specific Target Organ Toxicity (GHS Classification)

TLV: Threshold Limit Value

TSCA: Toxic Substances Control Act (U.S.)

TWA: Time Weighted Average (exposure for 8-hour workday)

U.S.: United States

VOC: Volatile Organic Compounds

WHMIS: Canadian Workplace Hazardous Materials Information System